

PRECISION COLOR. OUTDOOR READY.

Dedicated 3000K white channel with vivid RGB color mixing.

3W | 30 lm

15W | 1000 lm

24V DC | 30 deg beam | IP67



TECHNICAL SPECIFICATIONS

Compare the compact 3W and high-output 15W models.

SPECIFICATION	3W MODEL	15W MODEL
Input Voltage	24V DC	24V DC
Rated Power	3W	15W
Total Lumen Output	30 lm	1000 lm
Dedicated White Channel	3000K	3000K
Fixture Dimensions	Dia. 42 x 75 mm (1.65 x 2.95 in)	Dia. 75 x 100 mm (2.95 x 3.94 in)
Base / Bracket Dimension	85 mm (3.35 in)	85 mm (3.35 in)
Beam Angle	30 deg	30 deg
Weather Rating	IP67	IP67
Operating Temperature	-20 C to +60 C	-20 C to +60 C
Rated Lifetime	50,000 hours	50,000 hours
Warranty	3 years	3 years

IDEAL APPLICATIONS

LANDSCAPE

Trees, planters and exterior features

ARCHITECTURAL

Columns, facades and structural details

FEATURE ACCENT

Artwork, signage and display elements

COLOR EFFECTS

Residential and commercial atmosphere

IP67

OUTDOOR-READY PROTECTION

Protected against solid objects greater than 1 mm and short periods of immersion in water from 15 cm to 1 m.